

Valori standard per l'esecuzione delle esperienze

Serie E24

R(kΩ)	C (nf)	C(pF e μF)	C(pF) ordinata in senso crescente
0.1	0.001	1	1
0.11	0.0015	1.5	1.5
0.12	0.0022	2.2	2.2
0.13	0.0027	2.7	2.7
0.15	0.0033	3.3	3.3
0.16	0.0047	4.7	4.7
0.18	0.0056	5.6	5.6
0.2	0.0068	6.8	6.8
0.22	0.01	10	10
0.24	0.015	15	15
0.27	0.022	22	22
0.3	0.027	27	27
0.33	0.033	33	33
0.36	0.047	47	47
0.39	0.056	56	56
0.43	0.068	68	68
0.47	0.1	100	100
0.51	0.15	150	150
0.56	0.22	220	220
0.62	0.27	270	270
0.68	0.33	330	330
0.75	0.47	470	470
0.82	0.56	560	560
0.91	0.68	680	680

1	1			1000
1.1	1.5			1500
1.2	2.2			2200
1.3	2.7			2700
1.5	3.3			3300
1.6	4.7			4700
1.8	5.6			5600
2	6.8			6800
2.2	10			10000
2.4	15			15000
2.7	22			22000
3	27			27000
3.3	33			33000
3.6	47			47000
3.9	56			56000
4.3	68			68000
4.7	100			100000
5.1	150			150000
5.6	220			220000
6.2	270			270000
6.8	330			330000
7.5	470			470000
8.2	560			560000
9.1	680			680000
10	1000	1	μF	1000000
11	2200	2.2	μF	2200000
12	3300	3.3	μF	3300000
13	4700	4.7	μF	4700000

15	10000	10	μF	10000000
16	22000	22	μF	22000000
18	33000	33	μF	33000000
20	47000	47	μF	47000000
22	100000	100	μF	
24	220000	220	μF	
27	330000	330	μF	
30	470000	470	μF	
33	1000000	1000	μF	
36	2200000	2200	μF	
39	3300000	3300	μF	
43	4700000	4700	μF	
47	10000000	10000	μF	
51	22000000	22000	μF	
56				
62				
68				
75				
82				
91				
100				
110				
120				
130				
150				
160				
180				
200				

220
240
270
300
330
360
390
430
470
510
560
620
680
750
820
910
1000
1100
1200
1300
1500
1600
1800
2000
2200
2400
2700
3000

3300

3600

3900

4300

4700

5100

5600

6200

6800

7500

8200

9100

10000